

## P/N 0E33302

Wall mounted kit with AISI 304 stainless steel pneumatic piston pump R 1:1 - 30 l/min and AISI 304 stainless steel suction tube 1460 mm

### SECTORS OF USE

Agriculture, Automotive, Cleaning, Building and road construction, Industry, Mining, Lube trucks and transports

### FEATURES

|                               |                                                       |
|-------------------------------|-------------------------------------------------------|
| Ratio                         | 1:1                                                   |
| Flow rate                     | 30 l/min                                              |
| Compatible fluids             | suitable for antifreeze and windshield washing liquid |
| Suction tube upper body       | AISI 304 stainless steel                              |
| Suction tube                  | AISI 304 stainless steel                              |
| Air inlet connection          | G 1/4" (f)                                            |
| Fluid outlet connection       | G 1/2" (f)                                            |
| Air working pressure          | 6÷8 bar                                               |
| Average air consumption       | -                                                     |
| Noise level                   | -                                                     |
| Max deliverable oil viscosity | -                                                     |
| Bung adaptor                  | p/n 0E33434                                           |
| Suitable for drums or tanks   | modular                                               |
| Packing                       | No. 1 - 0,05 m <sup>3</sup>                           |
| Weight                        | 11,4 kg                                               |



